

this is proformance

# FLEX

## Cordless Tools



The inventor of the angle grinder!

All tools are brushless except models marked with \*. Models marked # are available in a carton or as a set in a carry case.

## CORDLESS DRILLS



### DD 2G 10.8-LDBC/2.5\*

#### 2 Speed Drill/Driver

Battery voltage: 10.8V  
No load speed: 0-350/1300rpm  
Torque: 17/34Nm  
2 x 2.5Ah batteries and charger



### PD 2G 18.0-EC LD/2.5 Set

#### 2-Speed Hammer Drill/Driver

Battery voltage: 18V  
No load speed: 0-500/1800rpm  
Torque: 35/65Nm  
2 x 2.5Ah batteries and charger



### PD 2G 18.0-EC FS55BC/5.0

#### 2-Speed Hammer Drill/Driver

Battery voltage: 18V  
No load speed: 0-600/2300rpm  
Torque: 50/75Nm  
2 x 5.0Ah batteries and charger



### PD 2G 18.0-EC /5.0 Set

#### 2-Speed Hammer Drill/Driver

Battery voltage: 18V  
No load speed: 0-600/2300rpm  
Torque: 56/90Nm  
2 x 5.0Ah batteries & charger

### PD 2G 18.0-EC HD/5.0 set

#### 2-Speed Hammer Drill/Driver with Turbo

Battery voltage: 18V  
No load speed: 0-700/2500rpm  
Torque: 70/158Nm  
2 x 5.0Ah batteries and charger



### DD 4G 18.0-EC /5.0 Set#

#### 4-Speed Drill Driver

Battery voltage: 18V  
No load speed: 0-460/910/2100/42 000rpm  
Torque: 64/135Nm  
2 x 5.0Ah batteries and charger



### CHE 18.0-EC C#

#### SDS+ Rotary Hammer Drill

Battery voltage: 18V  
No load speed: 0-1400rpm  
No. of blows: 0-4500bpm



### CHE 2-26 18.0-EC C#

#### SDS+ Rotary Hammer Drill

Battery voltage: 18V  
No load speed: 0-980rpm  
No. of blows: 0-4350bpm



## CORDLESS DRIVERS

### SD 5-300 4.0\*

#### Pocketsize Screwdriver

Battery voltage: 4V  
No load speed: 300rpm  
Integrated work lamp  
1/4" tool holder  
USB-C charging port



### ID 1/4" 18.0-EC HD C#

#### Impact Wrench

Battery voltage: 18V  
No Load Speed: 0-3700/4200rpm  
Torque: 58/104/237Nm



### DW 45 18.0-EC C#

#### Drywall Screwdriver

Battery voltage: 18V  
No Load Speed: 0-4500rpm  
Max torque: 28Nm



### DW 45 18.0-EC M/2.5 Set

#### Drywall Screwdriver

Battery voltage: 18V  
No Load Speed: 0-4500rpm  
Max torque: 28Nm



### IW 1/2" 18.0-EC C#

#### Impact Wrench

Battery voltage: 18V  
No load speed: 0-2500rpm  
Torque: 140/170/250Nm



### IW 1/2" 750 18.0-EC C#

#### 3 Gear Impact Wrench

Battery voltage: 18V  
No load speed: 0-2100rpm  
Torque: 150/200/750Nm



### IW 1/2" 950 18.0-EC C#

#### 3 Gear Impact Wrench

Battery voltage: 18V  
No load speed: 0-2100rpm  
Torque: 280/700/950Nm



### IW 3/4" 18.0-EC C#

#### 3 Gear Impact Wrench

Battery voltage: 18V  
No load speed: 0-1700rpm  
Torque: 300/590/1060Nm  
Max loosening torque: 1680Nm



## CORDLESS SAWS

### CS 62 18.0-EC C#

#### Circular Saw with Pendulum Hood

Battery voltage: 18V  
Blade diameter: 165mm  
Cutting depth: 0-62mm



### CS 45 18.0-EC C#

#### Compact Circular Saw with Pendulum Hood

Battery voltage: 18V  
Blade diameter: 128mm  
Cutting depth: 46.5mm



### JSB 18.0-EC C#

#### Jigsaw

Battery voltage: 18V  
Orbit rate, no load: 0-3500rpm  
Stroke: 26mm  
Max. material thickness, wood: 120mm



### SMS 190 18.0-EC#

#### Miter Saw

Battery voltage: 18V  
Max depth of cut: 66mm  
Mitre: 48°



### RS 25 18.0-EC#

#### One Hand Reciprocating Saw

Battery voltage: 18V  
No load speed: 3000rpm  
Swivel: 180°



### RSP DW 18.0-EC C#

#### Reciprocating Saw with Pendulum Stroke

Battery voltage: 18V  
Orbit rate, no load: 0-3000 rpm  
Stroke: 32mm



### MT 18.0-EC C#

#### Multitool

Battery voltage: 18V  
No-load oscillation: 10000-20000rpm  
Oscillation angle: 2°





**LB 125  
18.0-EC C#****Angle Grinder**

Battery voltage: 18V  
No load speed:  
9 000rpm  
Max. disc Ø:  
125mm

**L 125  
18.0-EC LD****Angle Grinder**

Battery voltage: 18V  
No load speed:  
10 000rpm  
Max. disc Ø:  
125mm

**DGE 25  
18.0-EC C#****Straight Grinder**

Battery voltage: 18V  
Speed selection:  
10 000/15 000/  
20 000/  
25 000rpm

**SE 125 18.0-  
EC/5.0 Set****Supraflex  
Grinder**

Battery voltage: 18V  
No load speed:  
660-1500 rpm  
Max. disc Ø: 125mm

**BME 18.0-EC C#****Trinoflex for Metal  
Surfaces**

Battery voltage: 18V  
No load speed:  
660-1500rpm  
Max. tool Ø:  
125mm

**PXE 80 10.8-EC/2.5  
P-Set****Rotary and Random  
Orbital Polisher**

Battery voltage: 10.8V  
No load speed: 400-5800rpm  
Max. disc: 80mm  
2 x 2.5Ah batteries & charger plus  
polishing accessories

**PE 150 18.0-EC/  
5.0 Set****Rotary Polisher**

Battery voltage: 18V  
No load speed: 150-1450 rpm  
Max. disc: 160mm  
2 x 5.0Ah batteries  
and charger

**XFE 15 150 18.0-  
EC/5.0 Set****Roto Random Orbit  
Polisher**

Battery voltage: 18V  
No load speed: 2300-3800 rpm  
Max. disc: 160mm  
Orbit rate, no load:  
4600-7600rpm  
2 x 5.0Ah batteries and charger

**XCE 8 125 18.0-  
EC/5.0 Set****Random Orbital polisher  
with Positive-Action Drive**

Battery voltage: 18V  
No load speed: 280-430rpm  
Max. disc: 160mm  
Orbit rate, no load: 5600-8600rpm  
2 x 5.0Ah batteries and charger

**VC 6 L MC 18.0\*****Compact Vacuum Cleaner**

Battery voltage: 18V  
Flow rate:  
1400l/min  
Max. vacuum:  
12000Pa

**BW 18.0-EC****Cordless Blower**

Battery voltage: 18V  
Max. flow rate:  
3.11m³/min  
Max. air speed:  
80m/sec

**CI 11 18.0\*****Cordless Inflator**

Battery voltage: 12 / 18.0 V  
Max. pressure: 11 bar  
Max. air flow rate:  
13l/m

**CF 18.0/230\*****Cordless Fan**

Battery voltage: 18V  
Air velocity:  
4.9m/sec  
Air volume:  
18.25m³/min

**DWL 2500 10.8/18.0\*****LED High CRI-Value  
Full-Spectrum Light**

Battery voltage: 10.8/18V  
Luminous flux:  
(10.8V) 300-2250 /  
(18V) 300-3000lm

**WL 2800 18.0\*****Floodlight Torch**

Battery voltage:  
12/18.0 V  
Luminous flux:  
1000/2800lm

**WL 300 18.0\*****Hand Torch**

Battery voltage:  
18V  
Luminous flux:  
150/300lm

**CL 2000 18.0\*****LED Spotlight**

Battery voltage:  
18V  
Luminous flux:  
1200/2000lm

**CL 5000 10.8/18.0\*****LED Spotlight**

Battery voltage:  
10.8/18V  
Luminous flux:  
5000lm  
5 brightness levels

**CL 10000 10.8/18.0\*****LED Spotlight**

Battery voltage:  
10.8/18V  
Luminous flux:  
10 000lm  
5 brightness levels

**TL 4000  
18.0/230\*****LED Spotlight  
with Tripod**

Battery voltage: 18V  
Luminous flux: 4000lm  
3 brightness levels

**MXE 18.0-EC  
WR2 120****2-Speed  
Cordless Mixer**

Battery voltage: 18V  
No-load speed: 0-780rp  
3-Level speed switch

**RD 10.8/18.0/230\*****Digital Radio for the  
Construction Site**

Battery voltage: 10.8/18.0 V  
DAB+ and FM  
Integrated Bluetooth  
AUX input & USB port and  
charger for smartphones



**ALC 3/360-G/R 10.8****360° Crossline Laser with Receiver Mode**

Battery voltage: 10.8V  
Max. range with receiver: 120mm  
Self-levelling range: 4°

**ALC 2/1-G/R****Self-levelling Crossline Laser with Receiver Mode**

Integrated battery  
Max. range with receiver: 70mm  
Self-levelling range: 4°

**ALC 3/1-G/R****Self-levelling Crossline Laser with Receiver Mode**

Integrated battery  
Max. range with receiver: 70mm  
Self-levelling range: 4°

**ADM 70 G****Laser Range Finder**

Precision:  $\pm 3$  mm  
Operating range: 0.05 - 70 m  
Laser class: 2

**ADM 100 G****Laser Range Finder**

Precision:  $\pm 3$  mm  
Operating range: 0.05 - 70m  
Laser class: 2

**ADL 60-P****Digital Spirit Level**

Measuring accuracy electronic:  
0°/90°: 0.05°  
Measuring accuracy electronic: 1-89°: 0.1°  
Measuring accuracy spirit level:  
0.029°

**ADL 120-P****Digital Spirit Level**

Measuring accuracy electronic: 0°/90°: 0.05°  
Measuring accuracy electronic: 1-89°: 0.1°  
Measuring accuracy spirit level:  
0.029°

**445886****Li-Ion Rechargeable Battery Pack:**

Battery voltage: 18V  
Battery capacity: 2.5Ah

**445894****Li-Ion Rechargeable Battery Pack:**

Battery voltage: 18V  
Battery capacity: 5.0Ah

**521078****Li-Ion Rechargeable Battery Pack:**

Battery voltage: 18V  
Battery capacity: 8.0 Ah

**418048****Li-Ion Rechargeable Battery Pack:**

Battery voltage: 10.8  
Battery capacity: 2.5Ah

**439657****Li-Ion Rechargeable Battery Pack:**

Battery voltage: 10.8V  
Battery capacity: 4.0Ah

**CA 10.8 / 18.0****Battery Charger:**

Battery voltage: 10.8/18V  
Battery capacity: 2.5/5.0/8.0Ah

**CA 18.0-LD****Battery Charger:**

Battery voltage: 18V  
Battery capacity: 2.5/5.0/8.0Ah

**CA 10.8****Battery Charger:**

Battery voltage: 10.8V  
Battery capacity: 2.5/4.0Ah

**P-Kit 55 R****Charging Station + 2 Batteries:**

Battery voltage: 10.8/18V  
Includes CA10.8/18.0 and 2 x 445894

**P-Kit 22 Q****Charging Station + 2 Batteries:**

Battery voltage: 18V  
Includes CA 18.0-LD and 2 x 445886



# The patented FLEX Proformance battery system delivers what it promises!

**Keep Control**

The smart technology controls and monitors the tool activity and the charging process, and provides information on the charging status via the LCD display.

**Therma-Tech™**

The unique, integrated cooling system ensures constant temperatures even under heavy loads.

**Power battery**

Powerful Li-Ion cells provide 18V power.

**Lithium-ion**

No self-discharge.  
No memory effect.

**EC motor**

Low-wear and brushless motor with EC technology for greater running performance, more power and more life.

All subject to technical changes & misprints (E & OE) . T & C's apply.

FLEX-Elektrowerkzeuge GmbH

For more information:

[www.flex-tools.com](http://www.flex-tools.com)

[info@flex-tools.com](mailto:info@flex-tools.com)

[www.newcopowertools.co.za](http://www.newcopowertools.co.za)

[info@newcopowertools.co.za](mailto:info@newcopowertools.co.za)

# FLEX

this is proformance